



REVISION RECORD			
REV.	CONTENT	MOD.	DATE
△	初版发行		

NOTES:
 Pitch : 5.0mm
 Rated Voltage : 250V
 Rated Current : 32A
 Withstand Voltage :
 AC2500V for 1 minute
 Insulation Resistance :
 500MΩ / DC500V
 Using Temperature Range :
 - 40℃ ~ + 105℃
 Wire range : 24~ 14AWG

技术要求:
 间距: 5.0mm
 额定电压: 250V
 额定电流: 32A
 耐电压值: AC2500V/min
 绝缘阻抗: 500MΩ/DC500V
 使用条件: -40℃~+105℃
 适用线规: 24~14AWG

5	J2-2-导电件	60J2BDD032AV-1	P	黄铜	镀镍
4	J2-2-弹片	60J2TDD032AV-1	2P	不锈钢	
3	J2-2-手柄	60J200Y0323V-1	2P	PA66-V0	
2	J2-2-盖板	60J3C910323V-1	1	PA66-V0	
1	J2-2-本体	60J3A910323V-1	1	PA66-V0	

NO.	NAME OF PART		NO. OF PART		Q' TY	MATERIAL	NOTES	
DES.	WY	DATE	2022/06/21	UNITS	MM	THIRD ANGLE PROJECTION		SHEET
CHK.		DATE		SIZE	A4			1 of 1
APP.		DATE		SCALE	1:1	DWG NO.	SP-2-4022001	REV: V0

上海有乐电气有限公司 Shanghai YouLe Electric Co., LTD	TITLE	J2-2-1120-00A
		J2-2-1120-成品

	pitch dimension			Nominal dimension					— □ ○
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	0 to 6	6 to 10	10 to 24	0 to 30	30 to 60	60 to 100	100 to 150		
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10