



REVISION RECORD			
REV.	CONTENT	MOD.	DATE
△	初版发行		

NOTES:
 Pitch : 5.0mm
 Rated Voltage : 250V
 Rated Current : 32A
 Withstand Voltage :
 AC2500V for 1 minute
 Insulation Resistance :
 500MΩ / DC500V
 Using Temperature Range :
 - 40°C ~ + 105°C
 Wire range : 24~ 14AWG

技术要求:
 间距: 5.0mm
 额定电压: 250V
 额定电流: 32A
 耐电压值: AC2500V/min
 绝缘阻抗: 500MΩ/DC500V
 使用条件: -40°C~+105°C
 适用线规: 24~14AWG

5	J2-2-导电件	60J2BDD032AV-1	P	黄铜	镀镍
4	J2-2-弹片	60J2TDD032AV-1	2P	不锈钢	
3	J2-2-手柄	60J200Y0323V-1	2P	PA66-V0	
2	J3-3-盖板	60J3C910323V-1	1	PA66-V0	
1	J3-3-本体	60J3A910323V-1	1	PA66-V0	

NO.	NAME OF PART	NO. OF PART	Q' TY	MATERIAL	NOTES
DES.	WY	DATE	2022/06/21	UNITS	MM
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1

上海有乐电气有限公司 Shanghai YouLe Electric C O., LTD	TITLE	J3-3-11MC-00A
		J3-3-11MC-成品

	pitch dimension			Nominal dimension					— □ ○
	over	over	over	over	over	over	over	over	
variable	0	6	10	0	30	60	100	150	□
range	to	to	to	to	to	to	to	to	
	6	10	24	30	60	100	150		○
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10