



REVISION		RECORD	
REV.	CONTENT	MOD.	DATE
△	初版发行		

NOTES:
 Pitch : 5.08mm
 Rated Voltage : 300V
 Rated Current : 15A
 Withstand Voltage :
 AC2500V for 1 minute
 Insulation Resistance :
 500MΩ / DC500V
 Using Temperature Range :
 -40℃ ~ +105℃

技术要求:
 间距: 5.08mm
 额定电压: 300V
 额定电流: 15A
 耐电压值: AC2500V/min
 绝缘阻抗: 500MΩ/DC500V
 使用条件: -40℃~+105℃

10	ZBD5-XXP标记号	ZBD5-XXP	1	PA66-V0			
9	LUK-左固定件	6LUKKOY0013V	1	PA66-V0			
8	LUK-右固定件	6LUKKOY0023V	1	PA66-V0			
7	LD1-2.5-弹片	6LD1B0001AV	2P	SUS301			
6	LD1-2.5-导电件	6LD1B0002AV	P	紫铜	镀雾锡		
5	LD1-2.5-按钮	6LD1A400204V	2P	PBT	橘黄		
4	LD1-2.5-XX壳体	6LD1C400203V	1	PA66-V0	绿色		
3	LD1-2.5-主体	6LD1A400203V	1	PA66-V0	绿色		
2	LZ3H-5.08-直针	1031B0002AV	2P	黄铜	镀雾锡		
1	LZ7-5.08-主体	1182A0YXXAV	2	PA66			
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES		
DES.	ZJL	DATE	2022/8/3	UNITS	MM	THIRD ANGLE PROJECTION	SHEET
CHK.		DATE		SIZE	A4		1 of 1
APP.		DATE		SCALE	1:1	DWG NO.	SP-1153A01 REV:V0
						TITLE	
				上海有乐电气有限公司 Shanghai YouLe Electric Co., LTD		LD700M-5.08-XXP-1Y-00A LD700M-5.08-成品	

	pitch dimension			Nominal dimension					—
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	to 6	to 10	to 24	to 30	to 60	to 100	to 150		
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10